CLAIMS

1. A primary alkaline battery, comprising:

a cathode comprising

manganese dioxide and

carbon particles comprising expanded graphite particles and non-expanded graphite particles, the expanded graphite particles having a kerosene absorption greater than about 2.7 milliliters per gram;

an anode;

a separator; and

an alkaline electrolyte.

- 2. The battery of claim 1, wherein the expanded graphite particles have a kerosene absorption greater than about 3.0 milliliters per gram.
- 3. The battery of claim 1, wherein the expanded graphite particles have a kerosene absorption greater than about 3.5 milliliters per gram.
- 4. The battery of claim 1, wherein the expanded graphite particles have a kerosene absorption greater than about 4.0 milliliters per gram.
- 5. The battery of claim 1, wherein the expanded graphite particles have a kerosene absorption greater than about 4.5 milliliters per gram.
- 6. The battery of claim 1, wherein the expanded graphite particles have a kerosene absorption greater than about 5.0 milliliters per gram.
- 7. The battery of claim 1, wherein the cathode comprises between about 75% and 25% of expanded graphite particles by weight and between about 25% and 75% of non-expanded graphite particles by weight.

25

30

5

10

- 8. The battery of claim 1, wherein the cathode comprises between about 60% and 40% of expanded graphite particles by weight and between about 40% and 60% of non-expanded graphite particles by weight.
- 5 9. The battery of claim 1, wherein the non-expanded graphite particles have an average particle size of less than about 40 microns.
 - 10. A primary alkaline battery, comprising:

a cathode comprising

manganese dioxide and

carbon particles comprising expanded graphite particles and non-expanded graphite particles, the expanded graphite particles having a BET surface area greater than about 5 ${\rm m}^2/{\rm g}$;

an anode;

a separator; and

an alkaline electrolyte.

- 11. The battery of claim 10, wherein the expanded graphite particles have a BET surface area greater than about $10 \text{ m}^2/\text{g}$.
- 12. The battery of claim 10, wherein the expanded graphite particles have a BET surface area greater than about $15 \text{ m}^2/\text{g}$.
- 13. The battery of claim 10, wherein the expanded graphite particles have a BET surface area greater than about $20 \text{ m}^2/\text{g}$.
 - 14. The battery of claim 10, wherein the cathode comprises between about 75% and 25% of expanded graphite particles by weight and between about 25% and 75% of non-expanded graphite particles by weight.

30

25

10

15. The battery of claim 10, wherein the cathode comprises between about 60% and 40% of expanded graphite particles by weight and between about 40% and 60% of non-expanded graphite particles by weight.

- 16. The battery of claim 10, wherein the non-expanded graphite particles have an average particle size of less than about 40 microns.
 - 17. A primary alkaline battery, comprising:

a cathode comprising

manganese dioxide and

carbon particles comprising expanded graphite particles and non-expanded graphite particles, the expanded graphite particles having a Scott apparent density less than about $0.08~\mathrm{g/mL}$;

an anode;

5

10

OODUBER DO

__20

25

30

a separator; and

an alkaline electrolyte.

- 18. The battery of claim 17, wherein the expanded graphite particles have a Scott apparent density less than about 0.07 g/mL.
- 19. The battery of claim 17, wherein the cathode comprises between about 75% and 25% of expanded graphite particles by weight and between about 25% and 75% of non-expanded graphite particles by weight.
- 20. The battery of claim 17, wherein the cathode comprises between about 60% and 40% of expanded graphite particles by weight and between about 40% and 60% of non-expanded graphite particles by weight.
- 21. The battery of claim 17, wherein the non-expanded graphite particles have an average particle size of less than about 40 microns.

22. A primary alkaline battery, comprising:

a cathode comprising

manganese dioxide and

carbon particles comprising expanded graphite particles and non-expanded graphite particles, the expanded graphite particles having a D_{50} particle size greater than about 35 microns;

an anode;

a separator; and

an alkaline electrolyte.

10

ngonest "oyl

<u></u>≟20

5

- 23. The battery of claim 22, wherein the expanded graphite particles have a D_{50} particle size between about 35 and about 100 microns.
- 24. The battery of claim 22, wherein the expanded graphite particles have a D_{50} particle size between about 40 and about 50 microns.
- 25. The battery of claim 22, wherein the cathode comprises between about 75% and 25% of expanded graphite particles by weight and between about 25% and 75% of non-expanded graphite particles by weight.
- 26. The battery of claim 22, wherein the cathode comprises between about 60% and 40% of expanded graphite particles by weight and between about 40% and 60% of non-expanded graphite particles by weight.
- 27. The battery of claim 22, wherein the non-expanded graphite particles have an average particle size of less than about 40 microns.
 - 28. A primary alkaline battery, comprising:

a cathode comprising

30

25

manganese dioxide and

expanded graphite particles having a kerosene absorption greater than about 4.4 milliliters per gram;

an anode;

5

10

199055 199054 "071120

a separator; and

an alkaline electrolyte.

- 29. The battery of claim 28, wherein the graphite particles have a kerosene absorption between about 5 and about 6 milliliters per gram.
- 30. The battery of claim 28, wherein the graphite particles have a kerosene absorption between about 5.2 and about 5.6 milliliters per gram.
 - 31. The battery of claim 28, wherein the graphite particles have a kerosene absorption about 5.4 milliliters per gram.
 - 32. The battery of claim 28, wherein the cathode comprises between about 2% and about 10% of expanded graphite particles by weight.
 - 33. The battery of claim 28, wherein the cathode comprises between about 3% and about 6% of expanded graphite particles by weight.
 - 34. The battery of claim 28, wherein the cathode comprises between about 80% and about 95% of manganese dioxide by weight.
 - 35. The battery of claim 28, wherein the cathode comprises between about 85% and about 90% of manganese dioxide by weight.
 - 36. The battery of claim 28, wherein the cathode further comprises non-expanded graphite particles.

30

25

Docket No.: 08935-245001 Client Ref. No.: M-4962

37. The battery of claim 36, wherein the cathode comprises between about 75% and 25% of expanded graphite particles by weight and between about 25% and 75% of non-expanded graphite particles by weight.

38. The battery of claim 36, wherein the cathode comprises between about 60% and 40% of expanded graphite particles by weight and between about 40% and 60% of non-expanded graphite particles by weight.

39. A primary alkaline battery, comprising:

a cathode comprising

manganese dioxide and

expanded graphite particles having a total pore volume greater than about 0.1 milliliter per gram;

an anode;

5

10

25

30

a separator; and

an alkaline electrolyte.

- 40. The battery of claim 39, wherein the expanded graphite particles have a total pore volume greater than about 0.15 milliliter per gram.
- 41. The battery of claim 39, wherein the expanded graphite particles have a total pore volume greater than about 0.2 milliliter per gram.
- 42. The battery of claim 39, wherein the cathode comprises between about 2% and about 10% of expanded graphite particles by weight.
- 43. The battery of claim 39, wherein the cathode comprises between about 3% and about 6% of expanded graphite particles by weight.
- 44. The battery of claim 39, wherein the cathode comprises between about 80% and about 95% of manganese dioxide by weight.

Docket No.: 08935-245001 Client Ref. No.: M-4962

1990EBB4 D71120

10

45. The battery of claim 39, wherein the cathode comprises between about 85% and about 90% of manganese dioxide by weight.

- 5 46. The battery of claim 39, wherein the cathode further comprises non-expanded graphite particles.
 - 47. The battery of claim 46, wherein the cathode comprises between about 75% and 25% of expanded graphite particles by weight and between about 25% and 75% of non-expanded graphite particles by weight.
 - 48. The battery of claim 46, wherein the cathode comprises between about 60% and 40% of expanded graphite particles by weight and between about 40% and 60% of non-expanded graphite particles by weight.
 - 49. The battery of claim 46, wherein the non-expanded graphite particles have an average particle size of less than about 40 microns.